Application of Synthetic Floc to Evaluate Sediment transport in the Decompartmentalization Physical Model Project

E. Tate-Boldt¹, C. J. Saunders¹, S. Newman¹, F. Sklar¹, C. Hansen^{1,2}, C. Zweig¹


¹South Florida Water Management District, West Palm Beach, FL, USA

²Florida International Univ., Miami, FL, USA

The Decompartmentalization Physical Model Project (DPM) is a landscape-level field test to reduce uncertainties associated with...

Experiments


- 6 Sepettido w
- 6 de impeortal
- RActis/teibution
 Management




Particle transport is essential for the development and maintenance of the Everglades ridge and slough landscape by redistributing entrained sediments.

The DPM project used a Dual Signature Tracer (DST) as a synthetic floc to measure sediment movement and redistribution.

- Manufactured by Partrac, Ltd., Glasgow, UK.
- Inert magnetic and fluorescent material.
- Hydraulically matched to the mean particle size and settling velocity of study region particles.




DST Preparation and Deployment




Spatial Experiments




 To measure spatial movement, 20-24 magnets were placed radially around the deployment location and retrieved the week after the initial flow.






Temporal Experiment







Conclusions

- The spatial experiment demonstrated that DST was entrained under high flows created by the S152 structure.
- Sediment moves unimpeded through the slough while movement through the ridge is moderated by velocity.
- While sediment movement into the ridge does occur, it only moved up to 10 meters into the ridge.

Acknowledgements

- Michelle Blaha, Claus Hansen, Christine Sciarrino, Kristin Seitz, Fabiola Santamaria, Eric Cline, and Michael Manna
- USACE, USGS, ENP, USFWS, FDEP, SFWMD
- Univ. Hawaii, Florida International University, ...