October 27-30, 2025

Coral Springs, FL

Hydrodynamic and Salinity Modeling in Florida Bay

Kelin Hu, Osama Tarabih & Ehab Meselhe, Tulane University

Matahel Ansar & Mirza Billah, South Florida Water Management District

10/29/2025












Objectives

- Develop a Delft3D hydrodynamic and water Quality model for Florida Bay in support of the Groundwater Exchange Monitoring and Modeling (GEMM) Project
- Serve as a quantitative platform for evaluating various factors affecting Florida Bay ecology
- Evaluate current and future water management practices
- Assess impact of SLR on surface and groundwater hydrology





Parameter	Delft3D		
Bathymetry & Topography	SFWMD Districtwide Digital Elevation Model (2023 Version)		
Boundary Condition	Offshore water level/salinity/temperature: Nested from the regional southern Florida model; Surface water /Groundwater sources: RSMGL		
Evapotranspiration	Calculated internally by D-Flow FM		
Wind	Wind NCEP/DOE Reanalysis II (T62 Gaussian grid, 6-hourly) https://psl.noaa.gov/data/gridded/data.ncep.reanalysis2.html * Other wind products or observations can be applied if needed		
Rainfall	Rainfall * Other rainfall products (e.g., NOAA Multi-Radar/Multi-Sensor System (MRMS)) or observations can be applied if needed		



Input



Hydrodynamics

Boundary condition

D-Flow FM

Coupled

D-Waves

(SWAN)

Horizontal surface (mesh info) Bottom shear stress Wind velocity Solar radiation

D-Water

Quality

Salinity Temperature

Water quality *

Tracer / Oxygen-BOD (DO)

Particulate inorganic matter (sediment)

Dissolved inorganic matter (NH4, NO3, PO4, AAP, ...)

Organic matter (POC, PON, POP, DOC, DON, DOP, ...)


Algae | Bacterial pollutants


Trace metals / Organic micro pollutants


Vegetation / Higher trophic levels

Output

* The specific water quality parameters to be simulated would depend on management questions and data availability.























Water level (m, NAVD88)Water level (m, NAVD88)

-0.5 Jan 2016

-0.5 Jan 2016

-0.5 Jan 2016

-0.5 Lan 2016

-0.5 Jan 2016

-0.5 Lan 2016

0.5

LRKF1

WRBF1

TBYF1

JBYF1

BWSF1

LBSF1

Oct


Oct


Oct


Oct


Oct

Oct













LRKF1


Daily water level comparison















Summary of Model Features

- 2D and 3D modes available
- Surface/ground water inputs
- Following features can be considered:
 - Impact of sea grasses
 - Coupling with SWAN wave model (3-level nesting computation)
 - Salinity and temperature
 - Integrated WQ processes for parameters such as DO, Chlfa, NH4, NO3, PO4, etc.
 - Major storm events
- Run time (1 year):
 - 2D: Flow + Sal + temp: 5 hours [+WQ: 10 hours]
 - 3D (10 layers): Flow + Sal + temp: 2 days [+WQ: 4 days]
 - Multiple scenarios can run simultaneously







Phase II

- Further model development (e.g., domain adjustment, forcings/boundary conditions, seagrass modeling, etc.), calibration and validation (both wet and dry periods).
- Forecast hydrodynamic, ecological, and hydrological responses to different climatic (e.g., storm surge events), operational, and environmental conditions in Florida Bay and its upstream watershed.
- Integrate with water management operations to minimize the occurrence of hypersalinity events in Florida Bay.

Freshwater Flows into Florida Bay


Daily flow data (1995–present) compiled from USGS records for 14 inlets into Florida Bay






Water Levels Data in Florida Bay


• 14 SECOORA stations providing fine temporal scale water level data (~ 6 minutes).






Water Levels Data in Florida Bay

14 DBHYDRO stations providing daily water level data.






Seagrass communities in Florida Bay

Maps representing spatial coverage of seagrass for individual years will be generated following the South Florida Fisheries Habitat Assessment Program (FHAP-SF) measurements

These maps will be input into Delft3D model to simulate the effects of different seagrass coverages on Hydrodynamics in Florida Bay

Total Seagrass



Seagrass modeling in Delft3D

- Seagrass is modeled in Delft3D by correcting the bed roughness using the equation proposed by Baptist (2005).
- Vegetation is modeled as rigid cylinders characterized by height, density, stems diameter, and drag coefficient.
 - · For the bed resistance, the Chezy coefficient is defined as:

$$C = C_b + rac{\sqrt{g}}{\kappa} \ln \left(rac{h}{h_v}
ight) \sqrt{1 + rac{C_D n h_v C_b^2}{2g}}$$

• The vegetation drag coefficient (λ) is a separate parameter calculated by:

$$\lambda = C_D n rac{h_v}{h} rac{C_b^2}{C^2}$$

Seagrass in Florida Bay (Hansen and Reidenbach, 2017)

Seagrass coverage	Canopy height (cm)	Density (shoots m ⁻²)	Blade width (cm)
Sparse	15.2 ± 2.0	259 ± 26	0.74 ± 0.27
Dense	37 ± 4.8	484 ± 78	0.80 ± 0.19