Greater Everglades Ecosystem RestorationApril 21-23, 2015

BISCAYNE BAY COASTAL WETLANDS RESTORATION BENEFITS

Presented by

Bahram Charkhian

Lead Environmental Scientist Coastal Ecosystems Section

sfwmd.gov


BISCAYNE BAY COASTAL WETLANDS PROJECT OBJECTIVE



- Re-establish productive nursery habitat
- Improve quantity, quality, timing and distribution of fresh water to Biscayne Bay
- Redistribute freshwater flow and minimize point source discharges
- Preserve and restore natural coastal glades habitat
- Re-establish connectivity between the coastal and adjacent wetlands
- Improve near-shore and saltwater wetland salinity regimes

OUTLINE

- Deering Estate Flow-way completed in 2012
- L-31E Culverts completed in 2010
- Temporary Pump Test Pilot Project for L-31E Flow-way - conducted October 2014-April 2015
- Congress authorized the project in 2014; federal appropriations are pending



L-31E Flow-way Temporary Pump Test



Deering Estate Flow-way Educational Wetland



L-31E Flow-way Showing Project Features



Cutler Flow-way Showing Project Features

DEERING ESTATE FLOW-WAY



The Deering Estate Flow Way is located in Southeastern Miami-Dade County

The goals include:

- Redirect up to 100 cfs freshwater to the coastal wetlands
- Re-hydrate the historic wetland and restore a more natural freshwater flow regime
- Establish an educational wetland

















Delineation of the Historical Freshwater Wetland Slough in Deering Estate and Areas of Inundation at Different Pump Rates Determined extent of inundation under various pumping rates

Estimated Acreage of Impounded Surface Water Under Different Pumping/Flow Rates within Deering Estate


Pumping Rate(cfs)	Duration	Estimated Acres	Percentage of
	of	of Impounded	Inundate Historic
	Testing	Surface Water	Remnant Wetlands
	(hours)		within Cutler Creek
0	5	0	0%
25	5	19	58%
50	5	25	76%
75	5	27	82%
100	5	31	94%

- □ Approximately 40,970 ac-ft. of fresh water redirected to historic remnant wetlands
- ☐ Timing of flows to the wetlands at Deering Estate has been improved


Discharges Through Deering Estate Pump Station (S-700)




 Reduced salinity in groundwater and surface water




Comparison of Surface Water Salinity at Deering Estate Wetland staff Gauges 1 and 3 Versus S-700 Daily Flow




Comparison of Salinity Concentrations in Groundwater Well #5
Near the Historic Remnant Wetlands of Deering Estate Versus
S-700 Daily Flow



Ecological Monitoring Stations for the Deering Estate Flow-way




 Groundwater stage rose noticeably at monitoring stations 2 and 5, and water levels varied according to pump operations



Comparison of Water Levels at Deering Estate Staff Gauges 1 and 3 within Vicinity of Historic Remnant Wetlands of Deering Estate Versus S-700 Daily Flow

IMPROVE NEAR-SHORE SALINITY REGIMES

✓ Reduced salinity in Cutler Creek, North Creek and nearshore at **Mouth of Cutler Creek**




- ■Deering EstateDaily Flow-way (S-700)Daily Flow (ac-ft)
- —Salinity Concentration at Mouth of Cutler Creek (Station CC2)
- —Salinity Concenetration Inside Cutler Creek (Station CC3)
- Salinity Concenetration Inside North Creek Creek (Station DNC01)

Comparison of Surface water Salinity at Deering Estate Nearshore Salinity Monitoring Stations (Mouth of Cutler Creek, Inside North Creek, and Inside Cutler Creek) Versus S-700 Daily Flow



BBCW L-31E PILOT PUMP TEST Project


- □ Purpose: divert water from point source discharge and redistribute through culverts to remnant tidal creeks
 - ✓ Minimize point source discharges
 - ✓ Improve environmental water delivery
 - ✓ Deliver freshwater to historic-tidal creeks
 - ✓ Hydrate coastal wetland areas
 - ✓ Improve nearshore salinity regimes





BBCW L-31E PILOT PUMP TEST Project

- Temporary pilot pump dry season operations started October 2014
- Water conditions allowed test to be extended from 3 months to 6 months
- Enhanced sheetflow to historic tidal creeks
- Pumping maintains L-31E canal stage at optimal level ~2.20 FT- NGVD29













BBCW L-31E PILOT PUMP TEST Project

Comparison of Monthly Total Flow in Acre-Feet (ac-ft.) Through L-31E Pilot Pump

- + 3,000 acre-feet of freshwater diverted from point source to overland flow
- Improved tidal wetlands and near shore salinity conditions




Nearshore Biscayne Bay Salinity Within Vicinity of L-31E Flow-way (RECOVER/BNP Monitoring Stations)



BBCW L-31E PILOT PUMP TEST Project

- Rehydration of coastal wetlands along east &west sides of L-31E Canal
- Reduced salinity and increased stage in groundwater





Comparison of Water Level and Salinity in Groundwater Monitoring Stations BBCW9GW1 and BBCW9GW2 within Vicinity of L-31E Pilot Project


The L-31E Culverts is located in Southeastern Miami-Dade County

The goals of the L-31E Culverts include:

- ✓ Minimize point source discharges
- ✓ Improve environmental water delivery
- ✓ Deliver freshwater to historic-tidal creeks
- ✓ Hydrate coastal wetland areas
- ✓ Improve nearshore salinity regimes



- Re-directed 11,944 ac-ft. fresh water from the C-102 and C-103 canals
- Enhancing sheet flow and rehydration fresh and saltwater wetlands



- Implemented vegetation monitoring to detect changes in response to increased freshwater flows
- Statistical analysis of data along two 100 meter transects in wetlands did not detect major changes
- However, expansion of sawgrass observed within project boundary




LOCATION OF TRANSECTS EAST OF THE LEVEE AT CULVERT S23-A AND S-23D

creases in sawgrass creage assessed by apping

013 mapping- 43.07 cres

015 mapping- 48.02 cres



expansion of sawgrass

Various species of birds, amphibians, nvertebrates, fish, and eptiles were observed







CONCLUSIONS

RESH WATER DELIVERED TO PROJECT

Deering Estate Flow-way Pump Station diverted 41,000 ac-ft. of water to coastal wetlands since December 2012

Temporary Pilot Pump Project diverted + 3,000 ac-ft. of water to L-31E Wetlands

L-31E Culverts diverted 11,944 ac-ft. of water from the C-102 and C-103 canals since November 2010

Timing of flows to the wetlands at Deering Estate Flow-way has been improved by supplying freshwater during the dry season

CONCLUSIONS

RE-ESTABLISH CONNECTIVITY BETWEEN THE COASTAL AND ADJACENT WETLANDS

The Deering Estate Flow-way and L-31E Culverts help restore the hydrologic connection to coastal wetlands

MPROVE NEAR-SHORE AND SALTWATER WETLANDS
SALINITY REGIMES

- Reduced salinity in groundwater and surface water
- L-31E Temporary Pilot Pump Test improved tidal wetlands and near-shore salinity conditions

CONCLUSIONS

ESERVE AND RESTORE NATURAL COASTAL GLADES
BITAT

letland stage and inundation have been increased

egetation within vicinity of Deering Estate Component esponding to changed hydrology with die-off of pland vegetation & emergence of wetland species

educed Non-Native Vegetation

xpansion of sawgrass observed

arious species of birds, amphibians, invertebrates, sh, and reptiles were observed

ACKNOWLEGEMENTS

iami-Dade County Parks, Recreation and Open baces Department

iami-Dade County Dept. Regulatory & Economic esources, Environmental Resources Management, estoration & Enhancement Section

eering Estate at Cutler and the Deering Estate bundation

scayne National Park

airchild Tropical Botanic Garden

liami-Dade County, Environmentally Endangered ands Program

